




ARMOR GUYS

• PROTECTED •



01-001

SPECIFICATION SHEET



ATTRIBUTES:

LINER

13g, Gray
100% **Taeki5**® Liner

COATING

Gray Polyurethane
Palm Coating

FEATURES:

- ANSI Cut Level A3
- Excellent Cut Resistance
- Excellent Heat Resistance
- Excellent Abrasion Resistance
- UV Light Resistance
- Lint Free
- Moisture Wicking

CATEGORY:

Taeki5®

APPLICATIONS:

- Aerospace
- Appliance Manufacturing
- Automotive Assembly
- HVAC/Sheet Metal
- Metal Fabrication
- Parts Assembly
- Pulling Electrical Wires

SPECIFICATIONS

LINER MATERIALS	Gray 100% Taeki5® Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CASE WEIGHT	15.30/lbs	16.30/lbs	17.62/lbs	18.72/lbs	19.16/lbs	21.16/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4X42C							
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

TECHNOLOGIES:



⚠ This product can expose you to N,N-Dimethylformamide-which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

Armor Guys reference number : 01-001

Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion Resistance	++	++	-
Cut Resistance	++	+	-
Heat Contact Resistance	+	x	+
Washing	++	+	-
UV Resistance	++	++	x
Lint Free	++	++	x
Any Color Available	++	-	-
Comfort	++	++	+
Variety of Coating Available Including Nitrile, PVC and Latex	++	-	+
Quality/Price Ratio	++	-	+
Total Performance	+29	+19	+12

*HDPE=High Density Polyethylene
**UHMWPE=Ultra High Molecular Weight Polyethylene

3	++	HIGH	1	-	LOW
2	+	MEDIUM	0	x	NO

Testing Method based on both CE and ANSI standard

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)